



SMART PRINTING SOLUTIONS

Technical Data Sheet

Parameters	Description	Storage
Item	SPS1106W	When stored in the original, unopened containers in a dry and cool place, the shelf life is as follows: (Shelf-life) In unopened original packaging: 12 months.
Material Base	Thermoplastic Synthetic Rubber	Packaging Specification
Core Application Categories	Label Adhesive	For pillow hot melt adhesive products: Bagged specifications: 20kgs/ctn, 25kgs/ctn and 27kg/ctn. Bulk cargo (unpackaged): Minimum palletizing quantity: 500kg per pallet. Optimal freight efficiency: 1MT (1,000kg) per pallet for bulk shipments. 20ft container palletized capacity: 17.28MT (17,280.00).
Specific Application Directions	Used for labeling various canned foods and beverages.	
Application Method	Nozzle, Roller	
Shape	Cuboid Block	
Color	Colorless and Transparent(Gardner 0-1#)	Additional information
Melting Viscosity	About 500mPa.s/160°C	
Softening Point	70±5°C	
Solid Content	100%	
Toxicity	Non-toxic	
Storage Life	12 months	
Recommended Working Temperature	125~160°C	1. Wear protective gloves and clothing to ensure safety due to high temperatures during product use. 2. Keep the melt tank lid tightly closed at all times to prevent debris from falling into the tank and affecting the usage effect. 3. The above information is provided based on our knowledge and experience. If materials or working conditions change, conduct thorough testing or contact our technicians for advice.

SMART PRINTING SOLUTIONS
ZAC MBAO CITE CHEIKH FAYE VILLA 352/ DP
NINEA : 009291593--- Tel : (221) 77 572 57 86

N° Compte : SN100 01022 005051960003 93 BANK OF AFRICA Dakar-SENEGAL
Email : smartprintingsolutionsenegal@gmail.com